





TEN

52503105
52503106
52503100
52503101





www.griferiarovira.com

1





2



27 mm.

67 mm.



3x



3




52503105

52503100



52503106

52503101



BAR

1 MÍN

5 MÁX


✓
1 A 3 BAR

° C

50 °

80 °

✓
50° A 65°



> 5 BAR




El incumplimiento de estas instrucciones exime de toda responsabilidad a Grifería Sanitaria Rovira s.a.



Grifería Sanitaria Rovira s.a. shall not be held liable for the non-compliance of these instructions.

Le non-respect de ces instructions exonère a Grifería Sanitaria Rovira s.a. de toute responsabilité.

4



5







6

IMPRESINDIBLE Y OBLIGATORIO VERIFICAR LA ESTANQUEIDAD Y EL CORRECTO FUNCIONAMIENTO DE LA PIEZA ANTES DE PONER EL REVESTIMIENTO.

VERIFYING TIGHTNESS AND CORRECT PERFORMANCE OF THE PIECE BEFORE TILING IS INDISPENSABLE AND COMPULSORY.

IL EST INDISPENSABLE ET OBLIGATOIRE DE VÉRIFIER L'ÉTANCHEITÉ ET LE BON FONCTIONNEMENT DE LA PIÈCE AVANT DE POSER LE REVÊTEMENT.



OK

